

VZH Series

Features

- 4 ϕ ~ 18 ϕ , 105°C, 2,000 ~ 5,000 hours assured
- Large capacitance with ultra low impedance capacitors
- Designed for surface mounting on high density PC board
- RoHS Compliance



Marking color: Black

Specifications

Items	Performance																													
Category Temperature Range	-55°C ~ +105°C																													
Capacitance Tolerance	±20% (at 120Hz, 20°C)																													
Leakage Current (at 20°C)	I = 0.01CV or 3 (μA) whichever is greater (after 2 minutes) Where, C = rated capacitance in μF V = rated DC working voltage in V																													
Tanδ (at 120Hz, 20°C)	<table border="1"> <thead> <tr> <th>Rated Voltage</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> <th>63</th> <th>80</th> <th>100</th> </tr> </thead> <tbody> <tr> <td>Tanδ (max)</td> <td>0.30</td> <td>0.26</td> <td>0.22</td> <td>0.16</td> <td>0.13</td> <td>0.10</td> <td>0.08</td> <td>0.08</td> <td>0.07</td> </tr> </tbody> </table> <p>When the capacitance exceeds 1,000μF, 0.02 shall be added every 1,000μF increase.</p>	Rated Voltage	6.3	10	16	25	35	50	63	80	100	Tanδ (max)	0.30	0.26	0.22	0.16	0.13	0.10	0.08	0.08	0.07									
Rated Voltage	6.3	10	16	25	35	50	63	80	100																					
Tanδ (max)	0.30	0.26	0.22	0.16	0.13	0.10	0.08	0.08	0.07																					
Low Temperature Characteristics (at 120Hz)	<p>Impedance ratio shall not exceed the values given in the table below.</p> <table border="1"> <thead> <tr> <th>Rated Voltage</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> <th>63</th> <th>80</th> <th>100</th> </tr> </thead> <tbody> <tr> <td rowspan="2">Impedance Ratio</td> <td>Z(-25°C)/Z(+20°C)</td> <td>4</td> <td>3</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> </tr> <tr> <td>Z(-55°C)/Z(+20°C)</td> <td>8</td> <td>5</td> <td>4</td> <td>3</td> <td>3</td> <td>3</td> <td>3</td> <td>3</td> </tr> </tbody> </table>	Rated Voltage	6.3	10	16	25	35	50	63	80	100	Impedance Ratio	Z(-25°C)/Z(+20°C)	4	3	2	2	2	2	2	2	Z(-55°C)/Z(+20°C)	8	5	4	3	3	3	3	3
Rated Voltage	6.3	10	16	25	35	50	63	80	100																					
Impedance Ratio	Z(-25°C)/Z(+20°C)	4	3	2	2	2	2	2	2																					
	Z(-55°C)/Z(+20°C)	8	5	4	3	3	3	3	3																					
Endurance	<table border="1"> <thead> <tr> <th>Test Time</th> <td>2,000 Hrs for $\phi D \leq 6.3\text{mm}$ & $8 \times 6.5\text{L}$ & $10 \phi \times 7.7\text{L}$; 5,000 Hrs for $\phi D \geq 8\text{mm}$</td> </tr> </thead> <tbody> <tr> <td>Capacitance Change</td> <td>Within ±30% of initial value</td> </tr> <tr> <td>Tanδ</td> <td>Less than 300% of specified value</td> </tr> <tr> <td>Leakage Current</td> <td>Within specified value</td> </tr> </tbody> </table> <p>* The above specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage applied for 2,000 ~ 5,000 hours at 105°C.</p>	Test Time	2,000 Hrs for $\phi D \leq 6.3\text{mm}$ & $8 \times 6.5\text{L}$ & $10 \phi \times 7.7\text{L}$; 5,000 Hrs for $\phi D \geq 8\text{mm}$	Capacitance Change	Within ±30% of initial value	Tanδ	Less than 300% of specified value	Leakage Current	Within specified value																					
Test Time	2,000 Hrs for $\phi D \leq 6.3\text{mm}$ & $8 \times 6.5\text{L}$ & $10 \phi \times 7.7\text{L}$; 5,000 Hrs for $\phi D \geq 8\text{mm}$																													
Capacitance Change	Within ±30% of initial value																													
Tanδ	Less than 300% of specified value																													
Leakage Current	Within specified value																													
Shelf Life Test	<table border="1"> <thead> <tr> <th>Test Time</th> <td>1,000 Hrs</td> </tr> </thead> <tbody> <tr> <td>Capacitance Change</td> <td>Within ±30% of initial value</td> </tr> <tr> <td>Tanδ</td> <td>Less than 300% of specified value</td> </tr> <tr> <td>Leakage Current</td> <td>Within specified value</td> </tr> </tbody> </table> <p>* The above specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1,000 hours at 105 °C without voltage applied.</p>	Test Time	1,000 Hrs	Capacitance Change	Within ±30% of initial value	Tanδ	Less than 300% of specified value	Leakage Current	Within specified value																					
Test Time	1,000 Hrs																													
Capacitance Change	Within ±30% of initial value																													
Tanδ	Less than 300% of specified value																													
Leakage Current	Within specified value																													
Ripple Current & Frequency Multipliers	<table border="1"> <thead> <tr> <th>Frequency(Hz)</th> <th>50, 60</th> <th>120</th> <th>1k</th> <th>10k up</th> </tr> </thead> <tbody> <tr> <td>Multiplier</td> <td>0.60</td> <td>0.70</td> <td>0.85</td> <td>1.0</td> </tr> </tbody> </table>	Frequency(Hz)	50, 60	120	1k	10k up	Multiplier	0.60	0.70	0.85	1.0																			
Frequency(Hz)	50, 60	120	1k	10k up																										
Multiplier	0.60	0.70	0.85	1.0																										

Diagram of Dimensions

Fig. 1





Fig. 2



Lead Spacing and Diameter

Unit: mm

ϕD	L	A	B	C	W	P ± 0.2	Fig. No.
4	5.7 ± 0.3	4.3	4.3	5.1	0.5 ~ 0.8	1.0	1
5	5.7 ± 0.3	5.3	5.3	5.9	0.5 ~ 0.8	1.5	1
6.3	5.7 ± 0.3	6.6	6.6	7.2	0.5 ~ 0.8	2.0	1
6.3	7.7 ± 0.3	6.6	6.6	7.2	0.5 ~ 0.8	2.0	1
8	6.5 ± 0.3	8.4	8.4	9.0	0.5 ~ 0.8	2.3	1
8	10 ± 0.5	8.4	8.4	9.0	0.7 ~ 1.1	3.1	1
10	7.7 ± 0.3	10.4	10.4	11.0	0.7 ~ 1.3	4.7	1
10	10 ± 0.5	10.4	10.4	11.0	0.7 ~ 1.3	4.7	1
12.5	13.5 ± 0.5	13.0	13.0	13.7	1.1 ~ 1.4	4.4	2
12.5	16 ± 0.5	13.0	13.0	13.7	1.1 ~ 1.4	4.4	2
16	16.5 ± 0.5	17.0	17.0	18.0	1.1 ~ 1.4	6.4	2
16	21.5 ± 0.5	17.0	17.0	18.0	1.1 ~ 1.4	6.4	2
18	16.5 ± 0.5	19.0	19.0	20.0	1.1 ~ 1.4	6.4	2
18	21.5 ± 0.5	19.0	19.0	20.0	1.1 ~ 1.4	6.4	2

Dimension: $\phi D \times L$ (mm)

Ripple Current: mA/rms at 100k Hz, 105°C

Impedance: Ω / at 100k Hz, 20°C

Dimension & Permissible Ripple Current

μF	Contents	63V (1J)			80V (1K)			100V (2A)		
		$\phi D \times L$	Imp.	mA	$\phi D \times L$	Imp.	mA	$\phi D \times L$	Imp.	mA
4.7	4R7	5×5.7	1.90	70						
10	100	6.3×5.7	1.20	130						
22	220	6.3×7.7	0.90	150	8×10	1.3	130	8×10	1.3	130
33	330	8×10	0.50	280	8×10	1.3	130	10×10	0.7	200
47	470	8×10	0.50	280	10×10	0.7	200	10×10	0.7	200
100	101	10×10	0.25	450	10×10	0.7	200	12.5×13.5	0.32	450
150	151	12.5×13.5	0.15	700	12.5×13.5	0.32	450	12.5×16	0.26	550
220	221	12.5×13.5	0.15	700	12.5×16	0.26	550	16×16.5	0.17	650
								18×21.5	0.15	950
330	331	16×16.5	0.082	900	16×16.5	0.17	650	18×16.5	0.15	850
								16×21.5	0.15	900
470	471	16×16.5	0.082	900	16×21.5	0.15	900	18×21.5	0.15	950
680	681	18×16.5	0.080	1,150	18×21.5	0.15	950			
		16×21.5	0.080	1,150						
1,000	102	18×21.5	0.06	1,250						

Part Numbering System

VZH series	470 μF	$\pm 20\%$	6.3V	Carrier Tape	8 $\phi \times 10L$	Pb-free and PET coating case
VZH	471	M	0J	TR	0810	
Series name	Capacitance	Capacitance Tolerance	Rated Voltage	Package Type	Terminal Type	Case size
						Lead Wire and Coating Type

Note: For more details, please refer to "Part Numbering System (SMD Type)" on page 13.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lelon:

[VZH-100M1CTR-0406](#) [VZH-100M1ETR-0406](#) [VZH-100M1JTR-0606](#) [VZH-100M1VTR-0506](#) [VZH-101M0JTR-0606](#)
[VZH-101M1ATR-0606](#) [VZH-101M1CTR-0606](#) [VZH-220M1ETR-0506](#) [VZH-220M1HTR-0606](#) [VZH-4R7M1VTR-0406](#)
[VZH-470M1ETR-0606](#) [VZH-470M1HTR-0607](#) [VZH-470M1JTR-0810](#) [VZH-470M1VTR-0606](#) [VZH-470M2ATR-1010](#)
[VZH-101M1ETR-0607](#) [VZH-101M1HTR-0810](#) [VZH-101M1JTR-1010](#) [VZH-101M1VTR-0810](#) [VZH-102M1ATR-1010](#)
[VZH-221M1CTR-0607](#) [VZH-221M1ETR-0810](#) [VZH-221M1HTR-1010](#) [VZH-221M1JTR-1313](#) [VZH-331M1ETR-0810](#)
[VZH-331M1HTR-1313](#) [VZH-471M0JTR-0810](#) [VZH-471M1ATR-0810](#) [VZH-471M1CTR-0810](#) [VZH-471M1ETR-1010](#)
[VZH-471M1JTR-1616](#) [VZH-681M1ATR-1010](#) [VZH-010M1HTR-0406](#) [VZH-100M1HTR-0606](#) [VZH-101M1HTR-1010](#)
[VZH-101M1KTR-1010](#) [VZH-101M1KTR-1313](#) [VZH-101M2ATR-1313](#) [VZH-102M0JTR-0810](#) [VZH-102M1CTR-1313](#)
[VZH-102M1ETR-1316](#) [VZH-102M1VTR-1616](#) [VZH-151M0JTR-0606](#) [VZH-151M1ATR-0606](#) [VZH-151M1CTR-0607](#)
[VZH-151M1ETR-0810](#) [VZH-151M1HTR-1010](#) [VZH-151M1JTR-1313](#) [VZH-151M1KTR-1313](#) [VZH-151M1VTR-0810](#)
[VZH-151M2ATR-1316](#) [VZH-151M2ATR-1616](#) [VZH-152M0JTR-1010](#) [VZH-152M1ATR-1313](#) [VZH-152M1CTR-1316](#)
[VZH-152M1ETR-1616](#) [VZH-220M0JTR-0406](#) [VZH-220M1ATR-0406](#) [VZH-220M1CTR-0506](#) [VZH-220M1JTR-0607](#)
[VZH-220M1VTR-0606](#) [VZH-221M0JTR-0607](#) [VZH-221M1VTR-1010](#) [VZH-222M0JTR-1313](#) [VZH-222M1ATR-1316](#)
[VZH-222M1CTR-1616](#) [VZH-222M1ETR-1616](#) [VZH-2R2M1HTR-0406](#) [VZH-330M0JTR-0406](#) [VZH-330M1ATR-0506](#)
[VZH-330M1CTR-0606](#) [VZH-330M1ETR-0606](#) [VZH-330M1HTR-0607](#) [VZH-330M1JTR-0810](#) [VZH-330M1VTR-0606](#)
[VZH-331M0JTR-0810](#) [VZH-331M1ATR-0810](#) [VZH-331M1CTR-0810](#) [VZH-331M1JTR-1616](#) [VZH-331M1KTR-1616](#)
[VZH-331M1VTR-1313](#) [VZH-332M0JTR-1316](#) [VZH-332M1ATR-1616](#) [VZH-332M1CTR-1616](#) [VZH-3R3M1HTR-0406](#)
[VZH-470M0JTR-0506](#) [VZH-470M1ATR-0606](#) [VZH-470M1CTR-0606](#) [VZH-470M1KTR-1010](#) [VZH-471M1CTR-1010](#)
[VZH-471M1HTR-1616](#) [VZH-471M1VTR-1316](#) [VZH-472M0JTR-1616](#) [VZH-472M1ATR-1616](#) [VZH-4R7M1HTR-0506](#)
[VZH-4R7M1JTR-0506](#) [VZH-680M1HTR-0810](#) [VZH-681M0JTR-0810](#) [VZH-681M1CTR-1010](#) [VZH-681M1ETR-1313](#)