

DAISSY-7X1-W2-WHT-MATT

~50° wide beam with tighter cutoff. 7X1 variant in matt white.

TECHNICAL SPECIFICATIONS:

Dimensions	279.5 x 39.6 mm
Height	20.3 mm
Fastening	pin, screw, clips
ROHS compliant	yes ⓘ

MATERIAL SPECIFICATIONS:


Component	Type
DAISSY-7X1-W2	Linear lens
DAISSY-7X1-SHD-WHT-MATT	Shade



Material	Colour	Finish
PMMA		
PC		matt

ORDERING INFORMATION:



Component		Qty in box	MOQ	MPQ	Box weight (kg)
CN17228_DAISSY-7X1-W2-WHT-MATT	Linear lens	432	72	72	0.0
» Box size:					



PHOTOMETRIC DATA (MEASURED):



SAMSUNG

LED LM28xB Series
FWHM 51.0°
Efficiency 92 %
Peak intensity 1.489 cd/lm
LEDs/each optic 2
Light colour White
Required components:





TEPCOMP group

LED PassivePAQ-L-1F35-SSA3-2.7K-840-3-DC
FWHM 65.0°
Efficiency 87 %
Peak intensity 0.760 cd/lm
LEDs/each optic 4
Light colour White
Required components:



TRIDONIC

LED LLE 24x280mm 750lm 8x0 LVD ADV1
FWHM 61.0°
Efficiency 91 %
Peak intensity 1.027 cd/lm
LEDs/each optic 4
Light colour White
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

www.ledil.com/where_to_buy

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

www.ledil.com/where_to_buy